


DP 1.2 4K CABLE — MALE TO MALE

OFC Material • Black PVC Jacket • Gold-Plated Connectors • OD 7.0 mm • 80-Braid + Aluminium Foil

1.5
M


3
M




DisplayPort



DisplayPort



HDMI



Mini DisplayPort



4K@60Hz



2K@144Hz



Plug&Play

Model No.	Length (Mtr)
XQ110	1.5 mtr
XQ111	3 mtr

- 4K@60 Hz on DP 1.2 2K4K60Hz.
- OFC conductors; 80-Braid + Aluminium-foil shielding.
- Gold-plated connectors; Black PVC jacket; OD 7.0 mm.
- Plug & Play- backward compatible.



INSTALLATION & BEST PRACTICES

- 7.0 mm outer diameter.
- Keep bends smooth – avoid sharp angles that stress the cores.
- Do not pull the cable by the connector.
- Grip the plug body when removing.
- Avoid running DP cables alongside high-power lines to reduce interference.

F.A.Q

Frequently asked questions

Does it support 4K@60?

Yes—when GPU & display support DP1.2 4K60

Audio over DP?

If both devices support it.

miniDP devices?

- For Mini DisplayPort sources, use a MiniDP ↔ DP adapter (active or passive depending on your setup).
- For long-distance runs at 4K@60 Hz, the maximum cable length depends on connected devices and installation environment.

@ info@compixs.com www.compixs.com

RIYADH-SAUDI ARABIA

DUBAI - UAE

GUANGZHOU - CHINA